



Enhance Your Signal Coverage with High Power 900/1800/2100MHz 2G/3G/4G/5G Booster

Our Product Introduction

for more products please visit us on signals-boosters.com

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: JIAYI
- Model Number: JY811
- Price: \$189.00/sets 1-9 sets
- Packaging Details: 1pcs repeater 900+1800+2100mhz
1pcs outdoor antenna
1pcs 20m cable
1pcs 10m cable
4pcs 3m cable with ceiling antenna
1pcs splitter 4way



Product Specification

- Type: 4G Signal Booster
- Network: 4g, GSM, 3G
- Product Name: Mobile Repeater
- Frequency: 900/1800/2100MHz
- Gain: 31dB
- Function: Signal Extender
- Application: Home Office Farm Hotel Ship
- Output Power: 30dBm
- Product Size: 33.5*25.5*8.5cm
- Weight: 5.8KG
- Color: Black
- Quality Warranty: 2 Yeara
- Highlight: 900 wireless signal booster,
900 industrial signal booster,
1800 wireless signal booster



More Images



Product Description

Products Description

Our Product Introduction



for more products please visit us on signals-boosters.com



Specification

Frequency Range		Uplink	Downlink
LTE 800MHz		832-862MHz	791-821MHz
GSM900MHz		890-915MHz	935-960MHz
1800MHz		1710-1785MHz	1805-1880MHz
2100MHz		1920-1980MHz	2110-2170MHz
2600MHz		2500-2570MHz	2630-2690MHz
Max. Gain		75dB ±1.5dB	80dB±1.5dB
Max. Output Power		22dBm±1.5dB	27dBm±1.5dB
Band width		Wide Band	
Manual Gain Control		31dB	
ALC		>25dB	
Ripple in Band		≤ 8dB	
Noise Figure		≤ 6dB	
VSWR		≤ 2.0	
Intermodulation		≤ -40dBc	
Spurious Emission	9KHz~1GHz	≤ -36dBm	
	1~12.75GHz	≤ -30dBm	
Time Delay		≤ 1.5 μs	
Frequency stability		≤ 0.01ppm	
MTBF		> 50000 hours	
Impedance		50 ohm	
Power Supply		AC 90-264V,DC 10V/10A	
Power LED		Power indicator	
Alarm LED	Red	Self oscillation or Strong input signal	
	Green	Normal	
Mechanical Specification			
RF Connector		N-Female	
Switch		Power Switch,Manual Gain Control Switch	
Cooling		Heatsink Convection cooling	
Humidity		< 90%	
Operating Temperature		-10°C ~ +55°C	
Environment Conditions		IP40	

Installation Type

Wall Installation

Size

439*268*58mm

Weight

< 8.5Kg

Installation Instructions


TEST YOUR BAND BEFORE PURCHASE

The Booster supports two major U.S. Carriers: **verizon** and **AT&T**
on Band 13 and Band 12/17, please confirm your cell phone band first.




For iPhone

1. Dial *3001#12345#*, press call button
2. Click "Serving Cell Info"
3. Check "Freq Band Indicator"



For Android Phone

1. Download APP: LTE discovery
2. Choose "SIGNALS"
3. Check "EARFCN"



If the result is band 12,13 or 17, you can choose this booster.

UNIVERSAL COVERAGE

INTELLIGENT AMPLIFICATION SIGNAL, SUITABLE FOR VARIOUS PLACES,
SIGNAL INSTANT FULL GRID

...



• THE CITY



• CITIES AND TOWNS



• INTENSIVE FLOOR



• HIGH-RISE OFFICE BUILDING



• THE BASEMENT



• VILLA



• THE MOUNTAINS



• RURAL

Shenzhen Jiayi Technology Co., Ltd.

+86 18825260857

18825260857@163.com

signals-booster.com

Factory Building 407, Building B, No. 41, Lixin Road, Danzhotou Community, Nanwan Street, Longgang District,
Shenzhen City, Guangdong Province, PR China Zip 518000